

DTEN D7 Dual 75"

All-in-One Video Conferencing and Collaboration Solution



SPECIFICATIONS

| | |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Software | Windows IoT |
| All-in-One | Multi-Touch Display x2 4K Camera 16-Microphone Array Integrated Speakers x2 |
| Display | Ultra HD 4K LED 75" x2 / 16:9 Capacitive Touch Screen Display |
| Camera System | 4K / Fixed Lens, Infinite Focus / F-value: 2.8 Diagonal Field of View (FOV): Up to 120 Degrees |
| Audio System | 16-Microphone Array Integrated Stereo Speakers Acoustic Echo Cancellation / Automatic Gain Control (AGC) / Automatic Noise Reduction |
| Network | Ethernet (RJ-45) 100/1000 Mbps Wi-Fi 802.11a/b/g/n, 802.11ac (2.4 and 5 GHz) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP Proxy Support |
| Inputs & Outputs | HDMI Out x 1 / HDMI In x 1 USB 3.0 x 2 3.5-mm Audio Jack x 1 / Microphone x 1 Ethernet LAN (RJ45) x 1 |
| VESA | 800 x 400 mm |
| Power | 100 to 240 V AC, 50 to 60 Hz |
| Product Dimensions | 132.7* x 37.9 x 2.19 in (337.06 x 96.29 x 5.54 cm) *Width may vary slightly depending on installation) |
| Product Weight | 167.2 lb (76 kg) (Product consists of two units. Each unit: 83.6 lb (38 kg)) |
| Packaging Dimensions | Product shipped in 2 boxes. Each box: 44.7 x 73.4 x 7.7 in (1135 x 1865 x 195 mm) |
| Packaging Weight | Product shipped in 2 boxes. Each box: 94.6 lb (43 kg) |
| Operating Temperature and Humidity | Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH |