

# DTEN GO with DTEN Mate


**DTEN GO**

|                                    |  |
|------------------------------------|--|
| Software                           | DTEN OS  |
| Display                            | Utilizes connected display   |
| Placement                          | Mount above or below TV or display   |
| Camera System                      | 4 Camera array: up to 32ft (10m) coverage<br>Horizontal field of view (HFOV): 160° combined  |
| Audio System                       | 12 Microphone array: up to 32ft (10m) coverage<br>HDMI & 3.5mm Audio Output<br>Acoustic Echo Cancellation<br>Automatic Gain Control (AGC)<br>AI-based Noise Cancellation<br>DTEN Smart Connect |
| Network                            | Ethernet (RJ-45)<br>WiFi 2.4Ghz & 5Ghz<br>IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static<br>HTTP/HTTPS Proxy Support  |
| Inputs & Outputs                   | Ethernet LAN (RJ45) x 1<br>3.5mm Audio Jack x 1<br>HDMI Out x 2<br>USB Type-C x 1  |
| In the Box                         | Power cord and adapter<br>HDMI cable x 2<br>Ethernet cable x 1   |
| Power                              | 100 to 240 VAC, 50 to 60 Hz  |
| Product Dimensions                 | 10.7 x 2.1 x 2.75 in (272 x 54 x 69mm)   |
| Product Weight                     | 1.3 lb (0.6kg)   |
| Packaging Dimensions               | 12.7 x 10.7 x 2.25 in (320 x 272 x 57mm)   |
| Packaging Weight                   | 3.55lb (1.61kg)  |
| Operating Temperature and Humidity | Operating Temperature 0°C to 40°C<br>Storage Temperature -10°C to 60°C<br>Operating Humidity 20% to 80% RH<br>Storage Humidity 10% to 60% RH   |


**DTEN Mate**

|                      |   |
|----------------------|---|
| Software             | DTEN Mate OS                                    |
| Display              | LED 10.1"<br>Capacitive Multi-touch Display     |
| Placement            | On table or handheld                            |
| Network              | WiFi 2.4Ghz & 5Ghz                              |
| Inputs & Outputs     | USB Type-C x 1                                  |
| In the Box           | Power cord and adapter                          |
| Power                | 100 to 240 VAC, 50 to 60 Hz                     |
| Product Dimensions   | 9.38 x 5.8 x 1.0 in (240 x 148 x 25 mm)         |
| Product Weight       | 1 lb (0.45kg)                                   |
| Packaging Dimensions | 12.6 x 6.8 x 1.5 in (320 x 173 x 38mm)          |
| Package Weight       | Approximately <2lb 1kg<br>(Official weight TBD) |

