

DTEN D7X 27

Workplace versatility with minimal IT complexity.



SPECIFICATIONS

Part Number	DBR2A27EX-S1
Software	Android OS 12
All-in-One	Multi-Touch 27" Display Native Zoom Rooms 3 Camera Array 8-Microphone Array Integrated Stereo Speakers
Bring Your Own Device (BYOD)	Smart Connect via single charging USB-C Cable (included) Extension of display via USB-C (computer must support USB-C Alt-mode DisplayPort) Touchback feature on Windows and Mac OS Use D7X Camera, Microphone, Touch and Speakers with any Software Client
Display	LED 27" 1080P/ 16:9 10 touch-points Al-based to improve the touch accuracy
Camera System	Combination HFOV: 160° Main Camera 90° PTZ and preset Zoom Rooms Auto framing Zoom Rooms Smart Gallery DTEN Smart Framing
Audio System	8-Microphone Array Internal Speakerphones
Inputs & Outputs	USB-C x1 USB 3.0 x 2; USB 2.0 x 1 Ethernet 1000 Mbps (RJ-45) x 1

DTEN D7X 27

Support for Zoom Contact Center/Kiosk and Zoom Rooms

POLICE STATE OF THE PARTY OF TH



SPECIFICATIONS CONT'D

Network	Ethernet (RJ-45) 1000 Mbps Wi-Fi 802.11a/b/g/n/ac/ax IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support Bluetooth 5.0
Power	100 to 240 V AC, 50 to 60 Hz
Product Dimensions	15.4 x 25.25 x 4.1 in (39.1 x 61.6 x 10.4cm)
Product Weight	7.35kg (16.2 lbs)
Packaging Dimensions	19.6 x 29 x 7.9 in (49.8 x 73.5 x 20cm)
Packaging Weight	10.6 kg (23.4 lbs)
Operating Temperature and Humidity	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
Services Available	DTEN Orbit Pro
In the Box	DTEN D7X 27 x1 Power cord x 5 (Type B,D,F,G,I) USB-C cable x 1 (6-ft) Product Guide